


- Nuts, Bolts & Sealer:**
- Bolts are DT1500 coated for corrosion resistance.
 - Walls Panels - Phillips head bolts, colour to match panels.
 - Roof & Ceiling Panels (Precoat) - Phillips head bolts, colour to match panels.
 - Roof & Ceiling Panels (Galvalume Plus/Galvanized) - HEX head (unpainted) bolts.
 - Sealer for the roof & ceiling panels - sidelaps & endlaps.
 - Sealer for the base of wall panels and bottom four feet of wall panel sidelaps.
 - *Sealer is a pressure sensitive tape 5/32" x 7/32". (Part # BT40)

- Standard Materials:**
- Roof panels are GALVALUME PLUS.
 - Ceiling panels are GALVALUME PLUS.
 - Wall panels are PRECOAT COLOURED.
 - Footing channels are GALVALUME only.
 - One ceiling access door.
 - Three elbows per downspout.

- Flashings:**
- Inside flashings for overhead doors, windows & walk door frames.
 - Exterior flashings for overhead doors and windows.
 - *(Flashings for windows are based on 5'-0" window height)
 - Standard lengths for overhead door exterior flashings are 16'-0".
 - Standard lengths for window exterior flashings are 11'-0".
 - Exterior flashings NOT supplied for walk doors unless requested by Builder.

- Liner Packages:**
- Liner panel profile is WM936 x 29ga Precoat Bone White or Cambridge White
 - Packages available are:


Economy: Trims for the framed openings and corners.



Standard: Trims for the framed openings, corners and top of the wall liner.



Deluxe: Trims for the framed openings, corners, top of the wall liner, and base of the wall liner.



Barrier: Trims for the framed openings, corners, top of the wall liner, and base of the wall liner. Foam closures for top and bottom of liner panels and butyl tape for all liner panel seamlines.

